

SHL-1200

Shear Magnet

The SHL1200 is a traditional shear lock which is ideal for single action doors which always rest at the same position and have good quality door closers fitted.

The construction of the SHL-1200 makes it suitable for aluminium and wooden doors - being very robust in construction and performance, the SHL-1200 provides a high level of security with a holding force of 1200kg.

The standard mounting method is flush, which enhances the security of the unit and does not alter the aesthetics of the door and its surroundings. An optional stainless steel surface housing is available to increase the flexibility of the unit.

Operating at 12 or 24Vdc, the shear lock operates with an initial in-rush current to ensure the armature is pulled up and located in its locked position. A minimum 2A power supply is required to power the SHL-1200 at 12Vdc, which allows for the in-rush current of 1.8A, this settles after locking to 630mA.

Monitoring is standard, a changeover relay signals that power is applied and the lock is bonded.

A varistor is built in to the electronics, which eliminates back EMF and protects sensitive controlling devices such as keypads and access control units

Key Features

- Robust construction
- Fail safe
- Monitored
- 1200kg holding force

Technical Specification

Dimensions	267 x 30 x 34mm (lock) 267 x 30 x 34mm (plate)
Environmental Voltage	-25°C to +70°C 12-24Vdc
Max current	1.8A in-rush @ 12Vdc 630mA resting @ 12Vdc 900mA in-rush @ 12Vdc 315mA resting @ 24Vdc
Monitoring	NO/NC relay

Part Numbers

SHL-1200	12/24Vdc Shear Magnet
----------	-----------------------

