

M-PRONTO

Entry Level Card Printer



Single feed for on-demand printing

The Magicard Pronto printer features a single card feed that enables you to produce a personalised card on demand in moments. It offers edge-to-edge and sharp image quality for simple and easy card printing in a compact and highly reliable package.

Rewrite technology

Using special rewrite cards, the Pronto colour ID card printer can print and erase the same card over and over in monochrome blue or black, ideal for visitors passes and temporary badges.

Budget friendly and secure

The Magicard Pronto printer delivers low cost printing and free card visual security as standard with four HoloKote® watermark designs. Security can be further enhanced with magnetic stripe and smart card encoding options.

Robust, compact and portable

The Magicard Pronto printer's aesthetic curves showcase an ultra-robust product. Its light and compact design makes it easy to transport to any location and reside on any counter or desktop.



2 year limited warranty

The Pronto is supplied with a free, 2 year depot warranty.

M-PRONTO

Entry Level Card Printer

High-performance, purpose-built composites for durability



USB interface



Rewritable technology



Magnetic stripe and smart card encoding options

Hand-feed slot

Patented HoloKote® watermark

Printer Specifications

Print mode	Colour dye sublimation, monochrome thermal printing and rewritable technology.
Visual security	The user has the option to print a HoloKote® security watermark across the card surface. When used with HoloPatch® cards, one area of the HoloKote watermark is highlighted as a high visibility security seal. A choice of 4 fixed HoloKote patterns are selectable from the printer driver.
Encoding security	Magnetic stripe encoding option. Smart card encoding: Contact chip, MIFARE, DESFire and iClass options.
Warranty**	2 years limited depot warranty.
Printer interfaces	USB rev 1.1 (USB 2.0 compatible).
Software drivers	Windows 2000 Professional (SP4), XP, Vista & 7 (32/64 bit compatible), Server 2003 R2 SP2, 2008 (32/64 bit compatible).
Weight	9.7 lbs (4.4kg).
Power source	External power supply 100-240V 50-60Hz autoranging.
Dimensions	270mm L x 215mm W x 233mm H (10.6" L x 8.4" W x 9.1" H).
Environment	Sheltered office environment 10°C to 30°C (50°F to 85°F).
Print speed	35 seconds for colour and 7 seconds for monochrome.

Consumables

Dye films	<ul style="list-style-type: none"> • YMCKO 5 panel dye film, 300 prints • YMCKO 5 panel dye film, 100 prints • Black & overcoat (KO) resin dye film 600 prints • Monochrome resin black dye film, 1000 images. Also available in *White, *Blue, *Red, *Gold and *Silver.
Cleaning kit	• 5 cleaning cards, 1 pen
Cleaning roller kit	• 5 cleaning rollers, 1 metal roller bar
Card types/thickness	CR80 and CR79 ISO PVC blank, magnetic stripe, self-adhesive, rewritable and HoloPatch cards. 0.51mm to 1.02mm (20mil to 40mil)

Variants

Pronto	MagiCard Pronto single-sided ID card printer.
Pronto Mag	MagiCard Pronto single-sided ID card printer with magnetic stripe encoder.
Pronto Smart	MagiCard Pronto single-sided ID card printer with smart card encoder.

Card security options



HoloKote®

A standard anti-counterfeiting watermark printed in a grid pattern across the entire card surface. The Pronto HoloKote features 4 standard designs.



HoloPatch®

HoloPatch cards have a highly reflective gold 'super diffuser' foil square that enhances the visibility of the overprinted HoloKote logo.



Magnetic stripe

The Pronto can be specified with ISO standard 7811 compatible HiCo encoding of magnetic stripe cards.



Smart card encoding

Smart card encoding options: Contact chip, MIFARE, DESFire, iClass.