

# SensorProx

## Mifare Readers

The SensorProx range of Mifare readers are the most complete range of readers on the market offering a suitable product for every application. All the SensorProx readers are compatible with all Sensor controllers making them very versatile and practical.

### Key Features

- Professional range for all applications
- Easy Installation
- Vandal resistant cast metal options
- Optical tamper switch
- Backlit keypad
- IP65 rated for external use

### SP-MF-SG

The size and fixings of the reader fits into a standard UK single gang electrical back box making it simple and neat to terminate. It is ideal for both internal and external applications.

### SP-MF-VRS

This reader is ideally suited for harsh environments as it is constructed from metal in one solid cast. Its low profile is attractive

### SP-MF-KPV

Ideal solution for card and pin use offering a very attractive solution with metal keys. This reader is very robust and comes as standard with backlighting allowing it to be used at night time. It is ideal for both internal and external applications.



# SensorProx

## Mifare Readers

	SP-MF-MINI	SP-MF-SG	SP-MF-VRS	KPV	SP-MF-KPV
<b>Dimensions (mm)</b>	Not Available	89(H)x89(W) x15(D)	120(H)x76(W) x27(D)	Not Available	120(H)x76(W) x27(D)
<b>Weight</b>		110g	440g		440g
<b>Read Range</b>		100mm	65mm		65mm
<b>Input Current (Standby)</b>		35mA @ 12vDC	35mA @ 12vDC		85mA @ 12vDC
<b>Input Current (Maximum)</b>		50mA @ 12vDC	50mA @ 12vDC		145mA @ 12vDC
<b>Voltage range</b>		5 to 16 vDC from a regulated supply	5 to 16 vDC from a regulated supply		5 to 16 vDC from a regulated supply
<b>Colour</b>		Black	Silver & Black		Silver & Black
<b>Material</b>		UV resistant poly-carbonate plastic	Metal		Metal
<b>LED Indicator</b>		One, Bi-Coloured	One, Bi-Coloured		Two, Coloured
<b>Buzzer</b>		Yes	Yes		Yes
<b>Operating Temperature</b>		-12°C to 60°C	-12°C to 60°C		-12°C to 60°C
<b>Max Range to controller</b>		100m	100m		100m
<b>To extend cable use</b>		Belden 9421 (22AWG, non-twisted)	Belden 9421 (22AWG, non-twisted)		Belden 9421 (22AWG, non-twisted)

### Contact us Today

Sensor Access Technology Ltd



+ 44 (0)1273 242355



sales@sensoraccess.co.uk