

SensorProx SF Panel Mount Readers

The SensorProx SF range of readers are practical and easy to install. All the readers are epoxy filled and weatherproof therefore suitable for indoor and outdoor applications. The SensorProx SF range uses smart card technology so cards can be used for multiple applications.

Key Features

- Mifare Compatible
- Secure Encrypted Format, cards & readers
- Built in Buzzer
- Smartcard technology
- Red, Green & Blue LED feedback

LED Feedback

The LED light changes Green for access granted or Red for access denied. This makes the readers very user friendly.

High Security

Both readers & cards are encrypted offering the user a secure solution with no card duplication

Modern Design


New smooth sleek black design makes this reader ideal for installs into UK single gang box.

Single Gang

The SF-PM are designed for UK single gang mounting.

Smartcard

The SensorProx SF range utilises read/write smart card technology. Cards can also be used for other applications such as biometric authentication, cashless vending and PC log on security.



SensorProx SF Panel Mount Readers



Technical Specification

Reader Specification

LED	Blue
Weatherproof	No
Reading Technology	Smart Card
Read Range	50mm
Frequency	13.56 KHz
Function	Read Only
Interface	Wiegand

Physical

SF-PM (reader)	54.4(H) x 59(W) x 25(D)mm
Width with mounting holes	77.2mm
Case Material	Plastic
Case Colour	Black

Environmental

Operating Temperatures	-30°C to +70°C
------------------------	----------------

Electrical

Operating Voltage	10 - 15 vDC
Operating Current	150mA (Max)



Part Numbers

SF-PM	SensorProx SF Panel Mount smart card reader
-------	---

Other reader formats & cards are available, please ask a member of staff for Part Numbers



Technical Tip

The SF readers have a configurable output allowing them to read the Full CSN of Mifare Classic, Mifare Plus and Desfire cards. These readers can also be purchased to read SensorProx and HID prox format cards.